



INTENTION CLICK CHEVRON 6 MM

Dare to manifest your tenacity with Intention Chevron, where each step forward is a declaration of purpose, a commitment to tread lightly upon the Earth. Warm, darker tones in contrast with honey-coloured oak characterizes the colour of Intention. Natural features such as knots and cracks emphasize the authentic, slightly rustic look of this floor which will contribute to creating a homely and relaxed interior.

PRODUCT DETAILS

Article Number / EAN-code	LTCCW2505-145 / 7393969303859
Construction	Click SPC LVT
Design	Chevron
Features	Microbevelled 4-sided, Wood design, Integrated sound reduction, Synchronized embossing
Width x Length x Thickness	145 mm x 665.4 mm x 6 mm
Weight per package	13.89 kg
Area per Package (m²) / Area per pallet (m²)	1.351 m² / 97.272 m²
Joint	Uniclic®
Installation method	Floating
Floor heating	Yes
Wear Layer Thickness approx. (mm)	0.7 mm
LRV / LRV Std1 / LRV Std2	20 / 1.5 / 3
Warranty	30 years

PRODUCT DETAILS

Collection	Sensation Collection
------------	----------------------

TECHNICAL PROPERTIES

Impact resistance (mm)	big ball), EN 13329	>1800 mm
Slip resistance	EN 13893	DS
Scratch resistance	EN16094	MSR-A1
Resistance against staining	EN 438-2	Grade 4-5
Residual indentation	EN ISO 24343-1 (2.5 h)	<0.15 mm
Reaction To Fire	EN13501-1	Bfl-s1
Product specification		EN 16511
Impact sound reduction	EN ISO 10140	19 dB
Dimensional stability	EN ISO 23999	< 0.15 % (80 °C/6 h)
Application	EN ISO 10874	23/34/42



Descriptions & Imagery: All samples, images and product description, plus photo and brochure specifications are therefor the sole purpose of giving an approximate idea of the items described in them.They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products.Your product may vary slightly from the images within this literature.