



FUSION CLICK HERRINGBONE 6 MM

Let Fusion Herringbone ignite your senses, merging timeless beauty with contemporary flair, creating spaces that resonate with harmony and style. Fusion offers a soft, pale blonde colour with undertones of honey and in combination with the calm, natural wood look creates a flooring design which will give any space a luxurious feel and impression.

PRODUCT DETAILS

Article Number / EAN-code	LTCHW2502-103 / 7393969303774
Construction	Click SPC LVT
Design	Herringbone
Features	Microbevelled 4-sided, Wood design, Integrated sound reduction, Synchronized embossing
Width x Length x Thickness	103.3 mm x 590.5 mm x 6 mm
Weight per package	10.04 kg
Area per Package (m²) / Area per pallet (m²)	0.977 m² / 109.424 m²
Joint	Uniclic®
Installation method	Floating
Floor heating	Yes
Wear Layer Thickness approx. (mm)	0.7 mm
LRV / LRV Std1 / LRV Std2	39 / 2.6 / 5.2
Warranty	30 years

PRODUCT DETAILS

Collection	Sensation Collection
------------	----------------------

TECHNICAL PROPERTIES

Impact resistance (mm)	big ball), EN 13329	>1800 mm
Slip resistance	EN 13893	DS
Scratch resistance	EN16094	MSR-A1
Resistance against staining	EN 438-2	Grade 4-5
Residual indentation	EN ISO 24343-1 (2.5 h)	<0.15 mm
Reaction To Fire	EN13501-1	Bfl-s1
Product specification		EN 16511
Impact sound reduction	EN ISO 10140	19 dB
Dimensional stability	EN ISO 23999	< 0.15 % (80 °C/6 h)
Application	EN ISO 10874	23/34/42



Descriptions & Imagery: All samples, images and product description, plus photo and brochure specifications are therefor the sole purpose of giving an approximate idea of the items described in them.They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products.Your product may vary slightly from the images within this literature.