



# OAK TAHINI PLANK

With light silver-golden tones of Tahini this light wood floor exudes rustic charm with its natural wood grain and knots in a darker contrast. Its organic and brushed texture enhances character, ensuring each plank is distinctive and bringing a warm yet airy ambiance to any room.

## PRODUCT DETAILS

|                                                         |                                |
|---------------------------------------------------------|--------------------------------|
| Article Number / EAN-code                               | LTCLR4016-193 / 7393969305303  |
| Product type / Construction                             | Wood Floors / Veneer floor     |
| Design / Wood species                                   | Plank / Oak                    |
| Surface Treatment                                       | Oil                            |
| Features                                                | Microbevelled 4-sided, Brushed |
| Width x Length x Thickness                              | 193 mm x 1980 mm x 10 mm       |
| Weight per package                                      | 24.3 kg                        |
| Area per Package (m²) / Area per pallet (m²)            | 2.675 m² / 133.75 m²           |
| Grading                                                 | Dynamic                        |
| Joint                                                   | Woodloc® 5G                    |
| Installation method                                     | Glue-down, Floating            |
| Floor heating                                           | Yes                            |
| Wear-layer material / Wear Layer Thickness approx. (mm) | Hardwood / 0.6 mm              |
| Resandable                                              | Not resandable                 |

## PRODUCT DETAILS

|                           |                                 |
|---------------------------|---------------------------------|
| Core material             | HDF                             |
| Backside material         | Veneer                          |
| LRV / LRV Std1 / LRV Std2 | 39 / 5 / 10                     |
| Warranty                  | 15 years                        |
| Warranty US               | 15 years                        |
| Collection                | Life Authentic Plank Collection |

## TECHNICAL PROPERTIES

|                                 |             |                 |
|---------------------------------|-------------|-----------------|
| Moisture content                | EN13183     | 7%±2%           |
| Minimun Mean Density kg/m³      |             | >800 kg/m³      |
| Reaction To Fire                | EN13501-1   | Bfl-s1          |
| Formaldehyde Emission           | EN717-1     | E1              |
| Content PCP                     | CEN/TR14823 | ≤ 5 x 10-6n     |
| Breaking Strength N/mm²         | EN1533      | NPD             |
| Biological Durability           | EN350-2     | Class 1         |
| CARB2                           |             | Compliant       |
| Thermal Resistance R-Value      |             | .07 (m2K/W)     |
| Thermal Conductivity            | EN12664     | 0,15 W/mK       |
| Resistance to indentation       |             | > 40 Newton/mm2 |
| Emission of formaldehyde (HCHO) | EN 14041    | E1              |



**Oil:** This floor should be oiled immediately after installation

*Descriptions & Imagery: All samples, images and product description, plus photo and brochure specifications are therefor the sole purpose of giving an approximate idea of the items described in them.They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products.Your product may vary slightly from the images within this literature.*